

## Type X-CUBE compact

□

### TOP PERFORMANCE, SMALL SIZE – COMPACT. EFFICIENT. TROX

The X-CUBE compact distinguishes itself by high quality in each and every detail and a whole spectrum of intelligent advantages

With the X-CUBE compact TROX has created a ready-to-operate and pre-configured air handling unit that combines the excellent features of the X-CUBE in the smallest of spaces. These units handle volume flow rates of 600 to 6,000 m<sup>3</sup>/h and offer a heat recovery efficiency of over 80 % (dry, to EN 308), hence they are the ideal solution for small and midrange applications.

Energy-efficient plug fans with EC motor ensure maximum efficiency and low sound power levels. An extensive range of accessories, such as a heating coil, a CO<sub>2</sub> sensor and a room control panel, can easily be connected to the X-CUBE control system.

#### Advantages at a glance

- Volume flow rates of 600 to 6,000 m<sup>3</sup>/h
- Maximum energy efficiency
- Powerful EC fans
- High level of hygiene (conforms to VDI 6022)
- Heat recovery with rotary heat exchanger or counter flow plate heat exchanger
- Air filtration with TROX minipleat or NanoWave filters
- Ready-to-operate unit (plug and play)
- Integral, bus compatible controls
- Intuitive operation
- Integration with advanced ventilation and air conditioning systems
- Optional weatherproof version with powder-coated metal roof to protect the unit and accessories, with perimeter drip edge, RAL 7012
- Made in Germany



## YOUR X-CUBE CONTACT

## TROX Italia S.p.A.

---



Società unipersonale soggetta a  
direzione e coordinamento di  
TROX GmbH

Sede legale: Via Mecenate 90 - 20138  
Milano

Cap. Soc. EUR 2.000.000

R.E.A. n.

659693

Reg.

Impr. MI, C.F. e P.IVA IT 00897380150

Casella di posta certificata: [trox@pec.it](mailto:trox@pec.it)

## Online-Services

---

> TROX Academy

---

> Your contact partner

---

> Online fault report

---

## Service-Hotlines

---

Telefono

+39 02-98 29 74.1

Telefax

+39 02-98 29 74 60