

The art of handling air

Type QLV




POLYGON CASING, 90° OR 180° AIR DISCHARGE, FOR COMFORT AND INDUSTRIAL ZONES

Polygon displacement flow diffusers

- Spigot diameter 160 – 630 mm, nominal height 500 – 1750 mm
- Volume flow rate range 17 – 915 l/s or 62 – 3295 m³/h
- Perforated plate, square pitch
- Circular duct connection
- Duct connection at the top or bottom
- Integral airflow straightener and conical equalising element

Optional equipment and accessories

- Wall mount
- Damper blade for volume flow rate balancing
- Exposed surface in RAL CLASSIC colours



Application

- Type QLV displacement flow diffusers are used as supply air units for industrial and comfort zones
- Attractive design element for building owners and architects with demanding aesthetic requirements
- Floor-standing installation on walls or in corners
- Low-velocity airflow, causing only low levels of induction and resulting in low-turbulence displacement ventilation.
- Excellent air quality in the occupied zone
- Draught-free and economical ventilation and air conditioning also of larger internal spaces such as shop floors or auditoriums, with several displacement flow diffusers in a regular arrangement
- For variable and constant volume flows
- For supply air to room air temperature differences from -6 to -1 K

Special characteristics

- Three-way or five-way air discharge
- Duct connection at the top or bottom
- Optional damper blade for volume flow rate balancing

Nominal sizes

- \varnothing D: 160, 200, 250, 315, 400, 500, 630 mm
- H: 500, 600, 800, 1000, 1250, 1500, 1750 mm

The art of handling air

Variants

- QLV-90: 90° air discharge
- QLV-180: 180° air discharge
- QLV-...-O: Spigot at the top
- QLV-...-U: Spigot at the bottom

Parts and characteristics

- Polygon casing
- Equalising element and airflow straightener that ensure a uniform supply air discharge
- Lip seal, optional for QLV-...-O

Attachments

- Damper blade for volume flow rate balancing

Accessories

- Lip seal
- Wall mount

Construction features

- Spigot suitable for circular ducts to EN 1506 or EN 13180

Materials and surfaces

- Top cover, base, spigot and side parts made of galvanised sheet steel
- S7: Top cover and base made of aluminium
- Corner and edge trims are extruded aluminium sections
- Airflow straightener made of plastic
- Equalising element made of synthetic fibres
- Lip seal made of rubber
- Surface powder-coated RAL 9010, pure white
- P1: Powder-coated, RAL CLASSIC colour
- S7: Surface galvanised

Standards and guidelines

- Sound power level of the air-regenerated noise measured according to EN ISO 5135

Maintenance

- Maintenance-free as construction and materials are not subject to wear
- Inspection and cleaning to VDI 6022

TROX Italia S.p.A.



Società unipersonale soggetta a
direzione e coordinamento di
TROX GmbH

Sede legale: Via Mecenate 90 - 20138
Milano

Cap. Soc. EUR 2.000.000

R.E.A. n.

659693

Reg.

Impr. MI, C.F. e P.IVA IT 00897380150

Casella di posta certificata: trox@pec.it

Online-Services

- > TROX Academy

- > Your contact partner

- > Online fault report

Service-Hotlines

Telefono
+39 02-98 29 74.1
Telefax
+39 02-98 29 74 60

TROX NEI SOCIAL WEB
